


ILUXUS
DESIGN

GENERAL CATALOGUE

DESIGN
TECHNOLOGY
COMFORT



Retro



Vintage



Helen



Toggle



Modular




B4 PushButton



Modular




VESTA



B4 KNX



Circle



Square



Actuators



TABLE OF CONTENT

EPHESUS



RoomController
PushButton



TouchPanel



EOZ



TouchPanel



ATHENE

PLATE COLLECTION

KREPIS PLATE


Krepis combines aesthetic design forms with **sharp design** lines. It has a unique design in the architectural concepts.

RADIUS PLATE

Radius reflects the elegance of **curved design** lines. It offers a unique concept of button designs.



KREPIS Mocha plate
SARISSA Brushed Copper button



RADIUS Matt Antique Copper plate
DIAMENTE Matt Antique Copper button

ATHENE

BUTTON COLLECTION

luxus
DESIGN

HERA
BUTTON



ODEON
BUTTON



CELLA
BUTTON



ATHENE

BUTTON COLLECTION

luxus
DESIGN

PERISTYL
BUTTON



DIAMENTE
BUTTON



SARISSA
BUTTON



ATHENE

SWITCH & SOCKET

COLLECTION

Athene series include many international socket types and electronic product mechanisms.



Brown
85x85x4 mm



White
85x227x4 mm



Dore
85x155.5x4 mm



Bronze
298x85x4 mm



Anthracite
227x85x4 mm



Matt Gold
227x85x4 mm



Euro-American
Socket 1M



German Socket
2M



British Socket
13A 2M



China Socket
16A 2M



900W Rotating
Dimmer 1M



Data RJ45 Cat6e
Socket 1M



USB Socket
1M



HDMI Socket
1M



Multistandard
Socket 2M



TV-SAT-FM
2M



Digital Thermostat
2M



Analog Thermostat
2M



Energy Saver
2M

ATHENE

COMBINATIONS

Frame Options (Vertical and Horizontal)




1 Gang : 85x85 mm



2 Gang : 85x155,5 mm



3 Gang : 85x226 mm



4 Gang : 85x298 mm

* 5 Gang Frame option dimensions : 85x370 mm

* All frames has 4 mm thickness


Function Options




Switches



Dimmer



Sockets



Sockets



RJ11/45



HDMI/USB



TV/SAT



Audio/Video



Thermostat



EnergySaver

luxus
DESIGN



Dimmer



Volume Control



ATHENE
VINTAGE

iLuxus
DESIGN

ELEGANCE
OF VINTAGE



THINNEST
PRODUCT
DESIGN


ATHENE
VINTAGE

luxus
DESIGN

SWITCH & SOCKETS

Create Your Special Style

Athene series: includes sockets suitable for
To all common switch-socket systems.
complete the decoration, provide
integrity with all products to be
used in the system.
switch sockets



ATHENE



VINTAGE

iLuxus
DESIGN

MULTI FUNCTION

More Function in Less Space

The Vintage series allows many functions to be used simultaneously in a single frame, saving space and saving time and budget. In this way, it gives your spaces a stylish and monospace look.



* Conventional and Modular System Production

ATHENE
VINTAGE

iLuxus
DESIGN

CUSTOMIZE SHAPED DESIGN

BeSpoke Product Solutions

Athene series: To meet the demands of projects or personal tastes; It allows product design in the desired shape and detail to meet almost unlimited different demands. This makes it possible for the frame of the product to be in the desired shape and size, as well as to include the requested design elements.




ATHENE
VINTAGE




iLuxus
DESIGN

PROJECT BASED PRODUCTION

Customize Your Designs

Athene offers special solutions for horizontal and vertical architecture with its outique design and craftsmanship. Its valuable customer architects, investor, designers, building contractors all the way from imaginations to project realization. Products and Solutions are genuinely engineered for Custom Design.






ATHENE
RETRO

luxus
DESIGN



SWITCH & SOCKETS
OLD STYLE
RETRO





ATHENE
HELEN

luxus
DESIGN



PURE
BEAUTY


 THINNEST
PRODUCT
DESIGN

ATHENE HELEN

FRAMES




Krepis



Radius

BUTTONS*




Lion



Wave

4 mm




Lion










Wave

8 mm



* 4, 6, 8, 10 mm thickness buttons options





ATHENE CIRCLE

iluxus
DESIGN




SPECIAL
ROUND DIAMETER
ø 78 mm




ATHENE CIRCLE

Conventional


Frame Options (Vertical and Horizontal)




1 Gang : 78x78 mm




2 Gang : 78x156 mm



3 Gang : 78x228 mm



4 Gang : 78x299 mm



5 Gang : 78x371 mm

All Frame has 4mm thickness



ATHENE

MODULAR



* 2M, 3M, 4M, 7M Frame Options




luxus
DESIGN



ATHENE


MODULAR

2M




2M Frame
85x85 mm

3M




3M Frame
118x85 mm

4M



4M Frame
142x85 mm

7M



7M Frame
208x85 mm

* 2M, 3M, 4M, 7M Frame Options




luxus
DESIGN

ATHENE B4
PushButton

iLUXUS
DESIGN


NEW
MODERN
DESIGN




4mm
THINNEST
PRODUCT
DESIGN

ATHENE B4 PushButton

FRAMES



Krepis




Radius

BUTTONS



10x10 mm



16x16 mm

Square





Ø16 mm




Ø10 mm

Circle



ATHENE B4
PushButton




BUTTONS
Round Diameter \varnothing 16 mm



BUTTONS
Round Diameter \varnothing 10 mm



With Push Button, the new product of Athene series, classic key elegance and KNX comfort are now together ...




RGB STATUS LED

PUSH BUTTON




SPECIAL
ICON SET
PROJECT BASED







Options

ATHENE B4


KREPIS



RADIUS



- 1 Gang : 85x85 mm
- 2 Gang : 85x155,5mm
- 3 Gang : 85x226 mm
- 4 Gang : 85x298 mm
- 5 Gang : 85x370 mm



Button height can be produced as requested.
The height in the photo is 1.8mm






SQUARE TOUCH SCREEN



Athene B4 Square New Touch screen Thermostat solutions..



ATHENE **B4**



ATHENE


MODULAR

ILUXUS
DESIGN




* 2M, 3M, 4M, 7M Frame Options

KNX




ATHENE

FRAMES



Krepis




Radius

BUTTONS & RINGS




Hera




Peristyl




Cella



Odeon



Diamente



Sarissa



Ring

Endless Combination

Frame, ring and bar buttons can be selected or changed in color or coating color as requested. Different color combinations can also be created this way.

COLORS

Brushed



BR
Brushed Bronze



BG
Brushed Gold



BC
Brushed Copper



AC
Antique Copper



BS
Brushed Steel




MC
Mocha



BW
Brown



PB
Parliament Blue



BB
Brushed Black

Pastel




RD
Red



AN
Anthracite



DR
Dore




WH
White

Color specific to projects...

It is possible to produce the desired RAL code values on a project basis.

ATHENE

DND UNITS



For hotel projects, we make special productions for customer and project needs and make the necessary visual customizations, ensuring that the projects make a difference with special products.



ATHENE DND UNITS





SPECIAL SOLUTIONS



i-luxus offers special solutions for special projects. It makes productions in accordance with the customer demands and projects. Whether on the sea, on land or for different places.






*


*

* We offer frame solutions for different brands.



SPECIAL SOLUTIONS

iLUXUS
DESIGN






SPECIAL
SOLUTIONS



SURFACE MENTAL BOX

It is possible to produce the desired dimensions for box.





VESTA50






VESTA50

Vesta offers special solutions for architecture with its Standart Conventional System


1-GANG
82x82 mm




2-GANG
82x153 mm



3-GANG
82x224 mm



4-GANG
82x295 mm




5-GANG
82x366 mm



COLOR OPTIONS

Brushed



Pastel





Color specific to projects...
It is possible to produce the desired RAL code values on a project basis.

VESTA50

i-luxus offers solutions suitable for every space project with its completely hand-made and niquely designed products. By combining technology with handcraft; brings together aesthetics, comfort and luxury. In addition to the conventional switch-socket series,





MUXUS
DESIGN



VESTA
MODULAR



VESTA

MODULAR



2M Frame
88 x 104 mm



3M Frame
88 x 127 mm



4M Frame
88 x 149 mm




7M Frame
88 x 215 mm



COLOR OPTIONS

Brushed





Pastel



Color specific to projects...
It is possible to produce the desired RAL code values on a project basis.

i-luxus offers solutions suitable for every space project with its completely hand-made and uniquely designed products. By combining technology with handcraft; brings together aesthetics, comfort and luxury.





EPHESUS

AESTHETIC LUXURY

KNX THERMOSTAT

Ephesus KNX Room controllers have a stylish and simple design. The dyeing process is done with its unique craftsmanship. Our devices, which are produced in two models with two and four buttons, can be easily mounted to the universal round or square plaster cases. At first sight, it is perceived as a KNX based thermostat controller. However, it is not only a thermostat, but also a KNX based room controller. The EPHESUS KNX Room Controller features a simple and friendly interface design with temperature, humidity and ambient light sensors. This ensures a high level of comfort and energy efficiency in your environment. With a single touch you can comfortably control air conditioning, lighting, curtains/blinds, activate/deactivate sound systems or scenario management.

EPHESUS
HANDMADE



EPHESUS

KNX THERMOSTAT

An aesthetic solution for air conditioning. Very low thickness design, available in 13 different colours. High quality product with push buttons and touch screen and room temperature and humidity sensor.



2 Gang Room Controller



4 Gang Room Controller



EPHESUS

KNX THERMOSTAT

GENERAL FEATURES

- ▶ Displaying environment humidity and temperature on the screen
- ▶ 4 or 8 integrated push buttons (for 2 or 4 gang models)
- ▶ 4 or 8 status LEDs on the push buttons for feedback of the operations (for 2 or 4 gang models)
- ▶ Switching, dimming, shutter&blind controls, HVAC controls, scenes and value control functions are available with push buttons
- ▶ Comfort, standby and economy modes are selectable
- ▶ Displaying the fan level of HVAC products on the screen
- ▶ Displaying window status with an external magnetic sensor
- ▶ KNX Certified with EN 50491 & EN 61000 standards

STATUS LEDS COMBINATION

Color White



Color Blue



Color Amber





CUSTOMIZE PRODUCTION



TAILOR-MADE

Design your Ephesus series with various symbols...
Create your own design.






EPHESUS PUSH BUTTON



3 Gang 6 Button



4 Gang 8 Button



5 Gang 10 Button



6 Gang 12 Button

PERFECT PLACEMENT

Everything was designed
where it should be and
to be controlled in the
most perfect way.

EPHESUS
ROOM CONTROLLER

150 cm



ATHENE
SWITCH

120 cm



luxus
DESIGN



150 cm

EOZ
TOUCH PANEL



120 cm

ATHENE B4 KNX
PUSH BUTTON



30 cm

ATHENE
SOCKET



EOZ IOT TECHNOLOGY

i.luxus
DESIGN

New Generation Touch Panel

EOZ Touch Panel, which brings many innovations to the world of Touch Panel, is the pioneer of new generation products. While allowing you to do many controls together with its user-friendly interface and the customizable icon structure, you can easily access the desired controls. Its drag-drop icon structure provides the ability to display the desired objects on the screens you want, which offers a unique touch panel usage opportunity.



KNX TOUCH PANEL

EOZ TOUCH PANEL

More Features

- * KNX New Chipset Technology
- * External 6 Channel Infrared Module (32 -40 KHz)
- * External 3 and 6 Output modules with 5A Output
- * Standart 6 Inputs (5V)
- * TCP/IP, Wifi
- * PoE supported
- * Dynamic UI application
- * Cloud Integration
- * IOS & Android mobile application control

7 " EOZ



NEW UI

Features

-  **IR Control**
All kind of IR devices are in your control. Enjoy...
-  **Air - Condition**
All kind of air condition devices can control over EOZ
-  **Cameras**
Watch all cameras over IP System from EOZ&Mobile App.

-  **Lighting**
Control every lighting object in KNX Bus System
-  **Intercom**
Communicate with intercom & SIP based devices over IP System.
-  **Security**
Stay in secure with every sensor devices which connected to EOZ

luxus
DESIGN

10.1 " EOZ



Fully supported all kind of KNX products



EOZ

MOBIL APLICACION

Mobile software and touch screens, if available. Control from anywhere in any time over the mobile phone for Android and IOS of your buildings.

Our EOZ software presents the same interface on all platforms. Every change you make to the master product is reflected simultaneously on the paired tablet software. You can design your own user interface from EOZ and use the same design over mobile apps. It includes control for Lighting, Shutter & Blinds, HVAC, Cameras, Alarm, Concierge and Scenarios. Connect over mobile app more than one EOZ panel. You can get instant push notifications as an alarm.



KNX ACTUATORS

ACTUATORS

12 GANG



LXA-112-16A
+ 12 input

20 GANG



LXA-120-16A
+ 12 input

16 GANG



LXA-116-16A
C-load 70uF

24 GANG



LXA-124-16A
C-load 70uF

POWER SUPPLY



LXA-164-000
640 mA

LED DIMMER 0/10 VOLT



LXA-148-010
DC 0-10 Volt

PUSH BUTTON INTERFACE

2 GANG



LXA - 132
2 Gang KNX Universal
Push Button interface

4 GANG



LXA - 134
4 Gang KNX Universal
Push Button interface

8 GANG



LXA - 138
8 Gang KNX Universal
Push Button interface

FLUSH MOUNTED ACTUATOR



LXA - 102 - 16A
2 Gang Switch + 2 Digital + 1 Analog Input 16A
KNX Actuator Flush-Mounted

LOGIC CONTROL



LGC-151
Logic Gateway




LGC-152
Logic Gateway

luxus
DESIGN


TECHNICAL
DATA

ATHENE


Assembly



Product assembly must be done according to this order. First of all, after the electrical connection of the Mechanism (M) to the Pedestal (2) is made, it is mounted to the case (1) with screws. Then, attach it to the holding points on the base frames (3). It is fully attached so that it can pass through. Mounting the product on the wall is completed.




Plasterboard casing or EU Norm square casing (1) should be used for product mounting. The product must be mounted on the case with the UP marking on the base (2) above. 3x16 metric screws (V) should be used to mount the product to the chassis. The tabs on the mechanism must match the tabs on the base.





MONTAGE



Athene Mounting Plate




HOLLOW WALL BOXES




2-modules 502E boxes can be installed side by side without the need for accessories.

ATHENE MODULAR


Product Dimensions



MOUNTING PLATE



WALL BOXES




ATHENE CIRCLE


Conventional

MONTAGE


Athene Mounting Plate



HOLLOW WALL BOXES



Frame Options (Vertical and Horizontal)




All Frame has 4mm thickness

Dimensions


VESTA 50

Boxes


FRAMES



CONCRATE WALL BOXES




HOLLOW WALL BOXES




2-modules 502E boxes can be installed by side without the need for accessories.


Dimensions




2 Modul (2M)




3 Modul (3M)





4 Modul (4M)




7 Modul (7M)




2M




3M



4M



7M



17.5 mm


VESTA MODULAR

FRAMES


MOUNTING PLATES

MODULES



Dimensions




7M




1M




2M




WALL BOXES




2M



3M




4M





7M


EPHESUS MONTAGE




Ephesus has a special montage plate for wall mount box. This plate should be used for wall mounting.



DIMENSIONS




EU 2M Standart Box




EU 2M Hollow Wall Box

EPHESUS ROOM CONTROLLER

LCD DESCRIPTION




DIMENSIONS




EPHESUS PUSH BUTTON

DESCRIPTION



DIMENSIONS



EOZ EXTENSION MODULES

IR GATEWAY

PRODUCT CHARACTERISTICS

- ▶ 6 IR Outputs
- ▶ Learn IR sensor
- ▶ Learn button
- ▶ Status LED
- ▶ Production in Germany, certified to ISO 9001

LXP-306-IRC

3&6 RELAY

PRODUCT CHARACTERISTICS


- ▶ 3 or 6 ON/OFF outputs
- ▶ Wide range of voltage switching capacity (up to AC 277V)
- ▶ Up to 5A load current
- ▶ 0.205-1.31 mm² solid wire or stranded wire cable connections
- ▶ Production in Germany, certified to ISO 9001

LXP-303-000


LXP-306-000

DIMENSION
L: 50mm
W: 35mm
H: 20mm

CONNECTION DIAGRAM



CONNECTION DIAGRAM



TOUCH PANEL EOZ

DIMENSIONS



7" TOUCH PANEL




10.1" TOUCH PANEL

EOZ Touch Panel has a special mounting box for wall montage. This box metal and provide screwless montage.

GENERAL FEATURES

- ▶ 7" and 10.1" capacitive touch panel
- ▶ 6 Infrared LED Outputs (optional)
- ▶ 6 dry contact inputs
- ▶ 3 or 6 Outputs DC 5V (optional)
- ▶ Lighting, air-conditioning, heating/cooling, valves, shutter/blind, intercom, concierge services, timer, scenarios, weather, forecast, security sensors, alarms, IP cameras, SIP video door phone properties
- ▶ Android 6 operating system
- ▶ Built-in microphone and speakers 2x3 W

CONNECTION DIAGRAM



TECHNICAL DATA

Product Detail	KNX Touch Screen - 24 V
Processor / Memory	Quad-core Cortex™ -A53 / 8GB e.MMC
Resolution	IPS-TFT - 1024X600 for 7" (LXP-370-000) / 1280X800 for 10.1" (LXP-310-000)
Mounting Position	7" Vertical / 10" Horizontal
KNX Connection	KNX Bus connection terminal
Connections	USB / Wi-Fi / RJ-45 Ethernet / DALI / IR Output (Optional)
Inputs	6 Dry Contact, Voltage 3.3V Pulsed, Current 1 mA
Outputs	3 or 6 Outputs (Optional), Switching Capacity (resistive load) - 5A 277 VAC
Dimensions	7 inch - L:134 W:208 H:30 mm / 10.1 inch - L:261 W:198 H:30 mm
Certification	CE Certified

POWER SUPPLY




LXA-164-30V

GENERAL FEATURES

- ▶ 640 mA output current
- ▶ Operating AC 150V – 275V @50-60 Hz
- ▶ 2 Power Outputs:
 - Output 1: Integrated KNX Choke (DC 30V, SELV)
 - Output 2: External Auxiliary Supply Output (30V, SELV)
- ▶ Short Circuit Protection for both outputs
- ▶ Overload Protection for both outputs

CONNECTION DIAGRAM



TECHNICAL DATA

Product Detail	KNX Power Supply 640 mA
Main Voltage	AC 230V ±15 % @ 50 Hz
Power Output	KNX Output Voltage - 28 ... 31 VDC (SELV) AUX Output Voltage - 28 ... 31 VDC (SELV) Max. Current - 640 mA
Operating Element	Reset Button - Left LED (Green) - Middle LED (Red) - Right LED (Red)
Width inspace unit	4 DIN Module (1 Module = 18 mm)
Dimensions / Weight	L:70 W:70 H:90 mm / 206 g
Certification / Standarts	KNX Certified / (EN50491-5-1/-2/-3)(EN50581)(EN61000-6-2/-3)(EN61558-1/-2-6)


MIX SWITCH ACTUATOR

12 GANG



PRODUCT CODE : LXA - 112 - 16A
 DESCRIPTION : 12 Gang + 12 Input KNX - Mix Actuator Switch - Shutter - Heating - Fan Coil C-Load 70 μ F
 COLOR : Cool Gray 9C
 SIZE : 180x90x67 mm - 10 Modul

20 GANG



PRODUCT CODE : LXA - 120 - 16A
 DESCRIPTION : 20 Gang + 12 Input KNX - Mix Actuator Switch - Shutter - Heating - Fan Coil C-Load 70 μ F
 COLOR : Cool Gray 9C
 SIZE : 180x90x67 mm - 10 Modul

16 GANG




PRODUCT CODE : LXA - 116 - 16A
 DESCRIPTION : 16 Gang KNX - Mix Actuator Switch - Shutter - Heating - Fan Coil C-Load 70 μ F
 COLOR : Cool Gray 9C
 SIZE : 180x90x67 mm - 10 Modul

24 GANG



PRODUCT CODE : LXA - 124 - 16A
 DESCRIPTION : 24 Gang KNX - Mix Actuator Switch - Shutter - Heating - Fan Coil C-Load 70 μ F
 COLOR : Cool Gray 9C
 SIZE : 180x90x67 mm - 10 Modul

CONNECTION DIAGRAM




TECHNICAL DATA

Product Detail	Mix Actuators With 12 Digital Inputs
Operating Mode	KNX Bus System
Current Consumption	<10 mA
Outputs	12 / 20 Outputs - AC 230V: @50/60 Hz - 16A, 102A Inrush
Operating Element	12 binary inputs - State Dry contact - Voltage DC 3,3V Pulsed
Width inspace unit	Character LCD with 3 Buttons
Dimensions / Weight	10 DIN Module (1 Module = 18 mm)
Certification / Standarts	L:67 x W:180 x H:90 mm - 578g
	KNX Certified / EN50491



FLUSH MOUNTED ACTUATOR




LXA-102-16A


GENERAL FEATURES

- ▶ 2 Relay Outputs (16A, 230VAC @50-60 Hz)
- ▶ 2 Digital (Dry Contact) Inputs
- ▶ 1 Analog Input
- ▶ Easy Installation to Flush Mounted Box
- ▶ Connection with colorful connection cables
- ▶ Lighting Function, Shutter&Blind Function
- ▶ Heating Function, Logic Function, Timing Function
- ▶ Data Type Converter Function
- ▶ Scene Function

CONNECTION DIAGRAM



SCALE DRAWINGS



TECHNICAL DATA

Product Detail	KNX Flush Mounted Actuator With Two Digital Inputs and One Analog Input
Main Voltage	KNX Bus System, no auxiliary supply
Outputs	2 Relay Outputs (16A, 102A Inrush Current, 230VAC @50-60 Hz)
Digital Inputs	2 Binary Inputs
Analog Input	PT1000, DC 0-10V
Operating Elements	Programming LED and button
Dimension / Weight	L:42mm W:42mm H:22mm / 34g with cables
Certification / Standarts	KNX Certified / EN50491

ANALOG I/O 0-10 VOLT




LXA-148-010

GENERAL FEATURES

- ▶ 8 Analog output channels DC 0..10V
- ▶ 4 Analog input channels
- ▶ 4 Digital input channels
- ▶ Dimming operations, HVAC operations
- ▶ Sensor connections: PT1000
(Brightness, Temperature, Rain, Humidity)
- ▶ Programming LED and buttons

CONNECTION DIAGRAM



TECHNICAL DATA

Product Detail	KNX Analog Inputs / Outputs
Main Voltage	KNX Bus System
Output	8 Analog Outputs, Voltage - DC 0-10 V Output Impedance - 35 Ohm, Current Source - max. 1 mA
Analog Inputs	4 Analog Inputs Voltage - Pt1000, NI1000, DC 0-10 V, Current - 0-20 mA via 500 Ohm shunt
Digital Inputs	4 binary inputs, Dry contacts, Voltage: DC 5V pulsed, Current 1mA
Width inspace unit	4 DIN Module (1 Module = 18 mm)
Dimension	L:70 x W:70 x H:90 mm
Certification / Standarts	KNX Certified / EN50491



PUSH BUTTON INTERFACE



LXA-132
2 Gang



LXA-134
4 Gang




LXA-138
8 Gang


GENERAL FEATURES

- ▶ Easy connection with colorful connection cables
- ▶ Possibility to incorporate dry contact data into the KNX line
- ▶ Switching, scene, counter, send value, shutter/blind and dimming operations
- ▶ Long press operation

CONNECTION DIAGRAM




SCALE DRAWINGS



TECHNICAL DATA

Inputs Product Detail	KNX Push Button Interface 4 Gang
Main Voltage	KNX Bus System
Inputs	8 Pos. 2.54mm Pin Header / Number 4
	Max. Cable length < 50m
Scanning Voltage	3.3V / Sensing Current = 0.1mA
Operations	Switch / Scene / Counter / Send Value / Shutter & Blind / Dimming
Operating Elements	Programming LED and button
Dimension / Weight	L:42mm W:42 mm H:12 mm / 22g with cables
Certification / Standarts	KNX Certified / EN50491

LOGIC CONTROL UNIT




LGC-151



LGC-152

CONNECTION DIAGRAM



GENERAL FEATURES

- ▶ 2 separate room controller functions
- ▶ 2 Separate occupancy communication functions
- ▶ 2 Separate window contact functions
- ▶ Occupancy contact start/end functions for thermostat on/off, heat/cool, operating mode, setpoint, and fan level.
- ▶ Window contact start/end functions for thermostat on/off, heat/cool, operating mode, setpoint, and fan level.
- ▶ AND, OR Logic operation functions. (15 pieces)
- ▶ The operating mode object type can be adjusted.
- ▶ Occupancy contact and window contact can be enabled with the object.
- ▶ 1 bit/2 bit/1 byte/2 byte Data converter objects functions (15 pieces)

TECHNICAL DATA

Mounting	60x60 mm standart switch junction
Connection	KNX Bus connection terminal
Operating Elements	Programming button
Operations	2pcs Room Cont. Func. (RTC), 2pcs Occupancy Cont. and Logics, 2pcs Window Cont. and Logics, 2pcs Window Cont. and Logics, Thermostat OnOff, Set Temp., 15pcs Data Conv. 15pcs Logic Gates
Temperature Range	Operation 0°C / +45°C , Storage -20°C / +70°C
Dimensions	L:20,34mm W:45,20mm H:45,20mm
Certification	KNX Certified

iluxus

DESIGN

iluxus Design

Yeditepe Caddesi No:81 34888 Ataşehir/İSTANBUL

info@iluxusdesign.com

www.iluxusdesign.com